


MODELS 741BR, 741SN, 741WH, 741BRFL & 741WHFL **DECORATIVE LIGHT / FANS**



A powerful ventilating fan with the look of an elegant glass light fixture.

FEATURES

LIGHT FIXTURE:

- Corrosion resistant finish Polished brass finish (Models 741BR & 741BRFL) Satin nickel finish (Model 741SN) Painted white finish (Models 741WH & 741WHFL)
- Frosted melon glass shade
- Close mount design
- Uses two 60 Watt maximum, type A, medium base bulbs (Models 741BR, 741SN & 741WH) or two 13 Watt fluorescent bulbs* (Models 741BRFL & 741WHFL). Bulbs not included.
- Vent openings in fixture base for exhaust fan
- Light fixture assembly is plug-in and removable

- Plug-in permanently lubricated motor
- Polymeric blower wheel

- Rugged, 26-gage galvanized steel construction
- Sturdy key-holed mounting brackets for quick, accurate
- Tapered, polymeric duct fitting with built-in backdraft damper for easy, positive duct connection and no metallic clatter

NOTE: For installation in ceilings up to 12/12 pitch.

U.L. Listed for use in insulated ceilings (Type I.C.) Use supply wiring rated for at least 90° C

NOTE: For installation in ceilings up to 12/12 pitch

SPECIFICATIONS

MODEL	VOLTS	AMPS	CFM	SONES	DUCT			
741BR	120	2.2	70	3.5	4" Round			
741SN	120	2.2	70	3.5	4" Round			
741WH	120	2.2	70	3.5	4" Round			
741BRFL	120	1.6	70	3.5	4" Round			
741WHFL	120	1.6	70	3.5	4" Round			

TYPICAL SPECIFICATION

Decorative Light/Fan unit shall be Broan Model 741BR, (741SN) (741WH) (741BRFL) (741WHFL).

Unit shall have galvanized steel housing with dual integral mounting brackets. It shall be ducted to a roof or wall cap.

Blower assembly shall be removable and have a permanently lubricated motor.

Light fixture assembly shall be plug-in, removable and include a frosted melon glass shade and a corrosion-resistant base with polished brass (Models 741BR & 741BRFL), satin nickel (Model 741SN), & painted white (Models 741WH & 741WHFL) finish.

Lamps shall be two 60 Watt maximum, type A, medium base, incandescent (Models 741BR, 741SN, & 741WH) or two 13 Watt fluorescent* (Models 741BRFL & 741WHFL).

Air delivery to be no less than 70 cfm and sound level no greater than 3.5 sones. Air and sound ratings shall be certified by HVI.

Unit shall be U.L. Listed for use in insulated ceilings (Type I.C.)

* Use only one of the following 13W fluorescent bulbs:


Sylvania CF13DD/827 G.E. F13DBX23T4/SPX27 **Philips** PL-C 13W/27/USA Osram CF13DD/827

Broan 97010729



HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-

shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in AMCA's state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.



Broan-NuTone LLC. 926 West State Street. Hartford. WI 53027 (1-800-637-1453)

REFERENCE	QTY.	REMARKS	Project	
			Location	
			Architect	
			Engineer	
			Contractor	
			Submitted by	Date