


## MODEL ZB80L VENTILATION FAN WITH LIGHT



### **FEATURES**

### UltraGreen™ Energy Saving DC Motor

- DC motor for efficiency well beyond ENERGY STAR® requirements.
- Multi-speed capability ideal for meeting ASHRAE 62.2, LEED and ENERGY STAR® for Homes requirements. Can be used to comply with CA Title 24, as well as local/spot ventilation needs.

#### UltraSilent™ Sound Technology

- HVI certified, best-achievable <0.3 Sone level provides nearly silent operation for a relaxing environment.
- State-of-the-art blower and duct outlet design smooths airflow.
- High tech DC motor designed for nearly silent operation.

### UltraSmart™ Control Technology

- Powerful operation maintained over a wide range of real-world installations (CFM ratings maintained through at least 0.25" static pressure).
- Infinitely adjustable low cfm setting allows precise adjustment to prevent over-ventilating and maximize efficiency.
- Adjustable time delay sets how long fan will run on high speed before returning to a continuous lower speed.
- · Rated for Continuous Operation.

### UltraLucent™ Lighting Technology

- Two, ENERGY STAR® qualified 18 watt (max) GU24, 3500K bulbs brightly illuminate room for most any task (bulbs included).
- One, 4 watt (max) C7 type night-light provides night-time convenience (bulb not included).
- Well-diffused, wide light dispersal floods room for maximum effectiveness and keeps bulbs from showing through lens.
- Enclosed reflector for minimal light visiblity through the grille.

### UltraQuick™ Installation Technology

- Unique telescoping mounting frame fits through retrofit drywall opening to allow easy installation from the room side. No attic access needed!
- Captive screws allow for easy new construction installation.
- Mounting frame positioning tabs provide easy vertical positioning for new construction.

- Easy to insert and remove snap-in housing. No screws required!
- Easy to insert and remove snap-in blower.
- Inside or outside duct connector and knockout plate mounting provides flexibility for new construction or retrofit

U.L. Listed for use over bathtubs and showers when connected to a GFCI protected branch circuit (ceiling mount only).

U.L. Listed for use in insulated ceilings (Type IC).


3-year warranty on product, 1-year warranty on bulbs.

# DIMENSIONS (Inches)









Broan-NuTone LLC Hartford, Wisconsin www.broan.com 800-558-1711

REFERENCE	QTY.	REMARKS	Project
			Location
			Architect
			Engineer
			Contractor
			Submitted by Date



### BROOM PERFORMANCE SPECIFICATIONS **MODEL ZB80L VENTILATION FAN WITH LIGHT**

### **AMCA LICENSED PERFORMANCE**

Airflov	1	Performance @ Static Pressure (Ps) - Inches Water Gage															
Rate Settin	Duct Size	0.100" Ps		0.125" Ps		0.250" Ps		0.375" Ps		0.500" Ps		0.625" Ps		Volts	Hz.	Nominal RPM	
(CFM)	3126	CFM	Sones	Watts	CFM	Sones	CFM	Sones	CFM	Sones	CFM	Sones	CFM	Sones			NEW
80	4" Round	80	< 0.3	8.3	80	0.3	79	0.9	79	1.6	62	2.1	34	2.6	120	60	1020
	6" Round	80	< 0.3	6.7	80	< 0.3	79	0.6	79	1.3	70	2.1	37	2.6	120	60	980



Performance ratings include the effects of inlet grille and backdraft damper. Speed (RPM) shown is nominal. Performance is based on actual speed of test. The sound ratings are loudness values in fan sones at 5' (1.5m) in a spherical free field calculated per AMCA Std. 301. Values shown are for Installation Type B: free inlet hemispherical sone levels. Performance certified is for Installation Type B: Free inlet, Ducted outlet.

### **HVI PERFORMANCE**

Airflow			6" Duct			4" Duct					
Rate	0.1 [	s - Static F	ressure (ir	H2O)	0.25 Ps	0.1 F	0.25 Ps				
Setting (CFM)	Airflow (CFM)	Sound (Sones)	Power (Watts)	Efficacy (CFM/Watt)	Airflow (CFM)	Airflow (CFM)	Sound (Sones)	Power (Watts)	Efficacy (CFM/Watt)	Airflow (CFM)	
80	80	< 0.3	6.0	13.3	80	80	0.3	7.3	10.9	80	
70	70	< 0.3	5.6	12.5	71	70	< 0.3	6.7	10.4	71	
60	60	< 0.3	4.7	12.7	63	60	< 0.3	5.7	10.5	61	
50	50	< 0.3	4.2	11.9	54	50	< 0.3	4.7	10.6	51	
40	40	< 0.3	3.4	12.3	39	40	< 0.3	3.9	10.7	38	
30	30	< 0.3	3.4	10.0	26	30	< 0.3	3.4	10.5	25	



HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in a state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

### **ELECTRICAL & WEIGHT**

Volts	Hz	Amps*	Shipping Weight (lbs.)
120	60	0.8	13.9

\* Total connected load





### **FAN CAPABILITY**

